

GS SERIES



GS14C/E



GS24C/E



GS30C/E



GS36C/E



GS60C/E

Remarks: C for Mechanical lock, E for Electronic lock.

FIRE PROTECTION



Fire resistant for 30-60 minutes up to 1400°F



Added layer of fireboard behind reinforced steel door and safe body



External welded solid steel strap hinges allow full fireboard protection



Door stripping expands when exposed to heat to protect against Fire and Smoke

BURGLARY PROTECTION



California DOJ standards



14-gauge steel body construction made by Robotically Welded



Re-locker mechanism for higher security



Pre-drilled for anchor kit



3-way locking system with 1" locking bolts




Drill resistant hardplate protecting critical spots



Anti-pry tabs work in tandem with safe's other security component to thwart pry attacks



Alarm system. If the safe is tampered with, the alarm will sound for 20 seconds



1
1" steel live action locking bolts are extended and retracted with the turn of handle.



2
Electronic Lock: Batteries are easily accessed from the front of digital lock.



3
Backup keys included, in case of lock.



4
Combo Lock: 3 number combination lock, provide higher security.



5
Door organizer provides extra storage for rifles, handguns, bullets and so on.

Model	External HxWxD(mm)	Steel Thickness	Gun Capacity	Fire Rating	Shelf	Bolts size
GS10C/E	1400x457x381	14ga.	Up to 10	40mins/1400°F	1	18 mm
GS14C/E	1400x508x432	14ga.	Up to 14	40mins/1400°F	1	18 mm
GS24C/E	1500x660x508	14ga.	Up to 24	40mins/1400°F	4	25.4 mm
GS30C/E	1500x711x508	14ga.	Up to 30	40mins/1400°F	4	25.4 mm
GS36C/E	1500x828x508	14ga.	Up to 36	40mins/1400°F	4	25.4 mm
GS45C/E	1500x1016x559	14ga.	Up to 45	40mins/1400°F	4	25.4 mm
GS60C/E	1829x1016x635	14ga.	Up to 60	60mins/1400°F	7	25.4 mm